1. PE-Xa service pipe 2. Temperature-resistent adhesive layer
3. Fine mesh, high temperature aramid fibre mesh
4. Temperature-resistent adhesive layer including oxygen diffusion barrier 5. Service pipe outer layer
6. Flexible Polyurethane-Foam (PUR) 7. Casing

Pre-insulated, flexible pipe system with fiber-reinforced medium pipe for use up to 115°C and 16 bar.

Thanks to the finer-meshed high-temperature fiber mesh made of aramid, the FibreFlex Pro 16 pipe system can be used up to a maximum operating temperature of 115 ° C and a pressure of up to 16 bar.

The FibreFlex Pro pipe system thus combines the advantages of a flexible pipe system with the operating properties of KMR steel pipe systems and therefore represents an innovative, cost-effective alternative.

®

Page 7

FibreFlex Pro pipe systems are designed for a service life of at least 30 years with the following temperature profile:

*29 years at 90°C + 1 year at 100°C + 100h at 115°C
or

Winter heating season 95°C + Summer heating season 85°C

Further temp./time profiles can be used in accordance with ISO 13760 (Miners rule).
The maximum operating temperature must not exceed 115°C.

Technical data:

Max. continuous
operating temperature:

Thermal conductivity:

Operating pressure:

Service pipe:

Thermal insulation:

Casing:

+95°C (seasonal)

0.021 W/mK

16 bar

PE-Xa with aramid
reinforcement

PUR, CFC-free
cyclopenthane-based

corrugated PE-LLD

Max. operating
temperature:

+115°C (variable*)

Type Dimension Casing

Max. Coil
length

Weight/
Meter

Bending-
radius
UNO/IS1 [mm] [mm] [m] kg r in m
50/111 47.6x3.6 111 410 2.00 0.90 63/126 58.5x4.0 126 300 2.40 1.00
75/142 69.5x4.6 142 220 (*440) 2.90 1.10
90/162 84.0x6.0 162 150 (*300) 4.00 1.20
110/162 101.0x6.5 162 150 (*300) 4.30 1.20
UNO/IS2 [mm] [mm] [m] kg r in m
50/126 47.6x3.6 126 300 2.20 1.00
63/142 58.5x4.0 142 220 (*440) 2.70 1.10
75/162 69.5x4.6 162 150 (*300) 3.50 1.20
90/182 84.0x6.0 182 86 (*170) 4.70 1.30
110/182 101.0x6.5 182 86 (*170) 5.00 1.20
DUO/IS1 [mm] [mm] [m] kg r in m
50+50/162 2x47.6x3.6 162 150 (*300) 3.60 1.20
63+63/182 2x58.5x4.0 182 86 (*170) 4.50 1.30
75+75/202 2x69.5x4.6 202 80 (*160) 5.70 1.40
90+90/225 2x84.0x6.0 225 75 (*150) 7.30 1.60
DUO/IS2 [mm] [mm] [m] kg r in m
50+50/182 2x47.6x3.6 182 86 (*170) 4.30 1.30
63+63/202 2x58.5x4.0 202 80 (*160) 5.30 1.40
75+75/225 2x69.5x4.6 225 75 (*150) 6.60 1.60
The specified maximum Coil lengths refer to the standard maxi-coil dimensions of (height x width) 2950x1200 mm. Project Coil lengths are available up to (*) = (height x width) 2950x2400mm.